



www.dkaudio.fr

E15-33 / E15-43



Two way speaker

E15-33

It is equipped with a 15" (38cm) low frequency speaker with a 3" moving coil and a 2" driver with a 3" moving coil on a constant directivity horn. Its shallow depth lets you install it in constricted areas. The low frequency speaker is an exclusive model designed by DKaudio.

This speaker usually comes in a passive version (mono-amp.), but an active filtering version (bi-amp.) is also available upon request.

E15-43

It is equipped with a 15" (38cm) low frequency speaker with a 4" moving coil and a 2" driver with a 3" moving coil on a constant directivity horn. Its shallow depth lets you install it in constricted areas. It's a slightly more "punchy" version of the E15-33. The low frequency speaker is an exclusive model designed by DKaudio.

This speaker usually comes in a passive version (mono-amp.), but an active filtering (bi-amp.) version is also available upon request.



www.dkaudio.fr

E15-33

E15-43

▶ TECHNICAL SPECIFICATIONS

Range: **11.25 meters**
Room size (seats): **30 to 100**
Impedance: **8 ohms**
Power capacity: **350 Watts AES**
Efficiency: **97 dB/1W/1m**
Bandwidth: **40Hz to 18kHz**
Low frequency speaker: **15" - 3" moving coil**
High frequency driver: **2" - 3" moving coil**
Directivity: **90° x 40°**
Dim. H x W x D: **1000 x 660 x 345mm**
Weight: **52.40kg**



▶ TECHNICAL SPECIFICATIONS

Range: **15.75 meters**
Room size (seats): **40 to 120**
Impedance: **8 ohms**
Power capacity: **450 Watts AES**
Efficiency: **99 dB/1W/1m**
Bandwidth: **40Hz to 18kHz**
Low frequency speaker: **15" - 4" moving coil**
High frequency driver: **2" - 3" moving coil**
Directivity: **90° x 40°**
Dim. H x W x D: **1000 x 660 x 345mm**
Weight: **54.90kg**



SHAPE DRAWINGS

