

E215-33 / E215-44



Two way speaker

E215-33

This traditional and high performing solution is equipped with dual 15" (38cm) speakers with 3" moving coil - 2" driver with 3" moving coil. It is designed for rooms from 50 to 200 seats. The low frequencies speakers are exclusive models especially developed by DKaudio.

This speaker is available in two versions: passive mono-amp, (E215-33P) or active bi-amp, (E215-33A).

E215-44

With its two 15" (38cm) speakers with 4" high quality moving coils (exclusive models designed by DKaudio) and its 2" driver with 4" moving coil, it litteraly represents the archetypal cinema sound system; a very crisp sound in a traditional and proven design.

This speaker is available in two versions: passive mono-amp, (E215-44P) or active bi-amp, (E215-44A).



E215-33 E215-44

TECHNICAL SPECIFICATIONS

Range: 20.10 meters

Room size (seats): 50 to 200 Impedance: 4 ohms / 8 ohms

Power capacity: 600 / 120 Watts AES

Efficiency: 100 / 110 dB/1W/1m Bandwidth: 40Hz to 18kHz

Low frequency speaker: 15" - 3" moving coil High frequency driver: 2" - 3" moving coil

Directivity: 90° x 40°

Dim. H x W x D: 1430 x 750 x 405mm

Weight: 70.20kg



TECHNICAL SPECIFICATIONS

Range: 32.10 meters

Room size (seats): 80 to over 300 Impedance: 4 ohms / 8 ohms

Power capacity: 800 / 180 Watts AES

Efficiency: 102 / 112 dB/1W/1m

Bandwidth: 35Hz to 15kHz

Low frequency speakers: 2 x 15" - 4" moving coil

High frequency driver: 2" - 4" moving coil

Directivity: 90° x 40°

Dim. H x W x D: 1430 x 750 x 405mm

Weight: 82.90kg



SHAPE DRAWINGS



