

#### E215-433



### Three way integrated speaker

# E215-433

This three way integrated speaker offers an amazing quality of sound reproduction.

The low frequencies are reproduced by two 15" (38cm) speakers with 4" moving coils, the mid-range way uses a 10" (26cm) speaker with a 3" moving coil guided by a horn with an exponential profile, which brings a great wealth of information, and a high frequency speaker via a 2" driver with a 3" moving coil guided by a constant directivity horn. The low and mid-range speakers are exclusive models designed by DKaudio

The E215-433 will easily fit behind a screen and will offer first class sound.

This three way speaker comes with a passive filtering between the low-mid range and a mid-high range driver (three ways bi-amp), which lets you replace the traditional two way bi-amp without having to withdraw lines of speakers and therefore improving the quality of the sound diffusion at a realistic cost.

However it can be delivered as a three way tri-amp and even, upon request, as a mono-amp with built-in passive filtering.



## E215-433

# TECHNICAL SPECIFICATIONS

Range: 22.95 meters

Room size (seats): 50 to 300 Impedance: 4 ohms / 8 ohms

Power capacity: 1200 / 350 Watts AES

Efficiency: 101 / 103 dB/1W/1m

Bandwidth: 35Hz to 18kHz

Low frequency speakers: 2 x 15" - 4" moving coil

Mid-range speaker: 10" - 3" moving coil - Exponential horn

High frequency driver: 2" - 3" moving coil

Directivity: 90° x 40°

Dim. H x W x D: 1520 x 698 x 465mm

Weight: 99.70kg

#### SHAPE DRAWINGS

